Reg. No: 00140 Issue: 1 Doc. Date: 22.06.2007 English Version



# BOILER DESCALER DELIME NC-412

### GENERAL

Product Name

**DELIME NC-412** 

Appearance Yellowish liquid

# **SPECIFICATIONS**

<u>PROPERTIES</u>	<u>LIMITS</u>
Density, g/cm <sup>3</sup> at 20 °C	1.10– 1.25
Solid Content, %	20 max

# **APLLICATIONS**

**DELIME NC-412** is a powerful boiler descaler and sludge remover. It is effectively to remove scales, which formed from carbonate salts, sulphate salts, silica deposits and iron deposits. It is safely to use in all types of heating system. For boiler descaling treatment, the optimal chemical use levels are 0.05-0.1kg in 1 tonne of water and operate the boiler as normal, in between the number of times of discharge boiler water must be increased. The same method needs to repeat for a few times until all the scales are completely removed from the boiler. For preventing scale forming, the ideal chemical use levels are 0.01-0.15kg per 1 tonne of water and operate the boiler as normal.

### PACKING

200kg per plastic drum. Shelf life: 2 years

# **TRANSPORT INFORMATION**

Not regulated

如需中文版产品介绍, 欢迎与我公司销售部连悉

The above information is, to the best of our knowledge, true and accurate, but any recommendations or Suggestions, which may be made, are without guarantee, since the conditions of use are beyond our control.