Reg. No: 00611 Issue: 1 Doc. Date: 18.05.2007 English Version





SWR 1 & 2

PRODUCT INFORMATION

DESCRIPTION

NOBLAZE [®] SWR-1 and NOBLAZE [®] SWR-2, which come in separate packages, they have to combine and form highly effective wool flame retardant. In wool treatment with NOBLAZE SWR-1 & SWR-2, excellent results were shown include high efficiency, low toxicity, durable for washing and easy handling.

SPECIFICATIONS

Parameter	NOBLAZE [®] SWR-1	NOBLAZE [®] SWR-2
Appearance Active Content, %	Yellow liquid 48.7	Clear liquid 40
pH @ 25 °C	< 2	< 2
Ionicity	Anion	Anion

APPLICATIONS

NOBLAZE [®] SWR-1 and NOBLAZE [®] SWR-2 are outstanding durable flame-retardants for wool products. For wool treatments, NOBLAZE chemicals can be diluted with water to the desired concentration and then applied by dipping techniques as shown as the following procedures.

USAGE PROCEDURES

- 1. Prepare fresh water in a tank and increase the water temperature until 85 °C.
- 2. Add 5% of NOBLAZE $^{\circledast}$ SWR-1 and 15% of NOBLAZE $^{\circledast}$ SWR-2 into the water tank and stir evenly.
- 3. Maintain the mixture at a pH below 3; which can be adjusted by adding citric acid or formic acid.
- 4. Place the wool into the mixture, then increase the temperature until 95°C and maintain it for 30-35 minutes.
- 5. Later discharge the mixture and rinse the wool with fresh water at 40°C for 5-10 minutes until the pH value has increased to 4 and this wool treatment is considered has completed.

CAUTIONS

- 1. In the wool treatment procedures, the chemicals such as sulphuric acid, glauber salt and phosphate softener or detergent cannot be used.
- 2. During the rinsing process, the wool cannot be neutralized by alkaline solution; it only can be rinsed with fresh water until the pH reach to 4.

Planet Chemicals Pte Ltd

Reg. No: 00611 Issue: 1 Doc. Date: 18.05.2007 English Version



3. Since NOBLAZE [®] SWR-1 and NOBLAZE [®] SWR-2 are acidic, it may cause burns on eyes and skin, when undergoing treatment process personal protective equipments must be worn.

PACKING

125kg or 170kg per drum in plastic drum. Shelf life: 1 year

TRANSPORT INFORMATION

NA

如需中文版产品介绍, 欢迎与我公司销售部连悉

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Planet Chemicals Pte Ltd. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patents.