

Reg. No: 00112  
Issue: 2  
Doc. Date: 04.2008  
English Version



## SEQUESTON

# PAC-HV 2

### GENERAL

Chemical Name	High Viscosity Polyanionic Cellulose
Product Description	A high molecular weight polyanionic cellulose polymer
CAS No.	9004-32-4
Appearance	Off-white free flowing powder

### SPECIFICATIONS

<u>Properties</u>	<u>Typical Value</u>
Active Content,% (dry basis)	70 min
Degree of Substitution	0.9 min
pH (1% solution)	7-10
Moisture Content, %	8 max
Bulk Density (kg/m <sup>3</sup> )	600-900
Salt Content, %	20 max

### PERFORMANCE

As per API-131 (PAC HV) procedure  
Apparent Viscosity (cPs): 25 min

### FEATURES & BENEFITS

Increases viscosity and provides fluid loss control to fresh water and salt based drilling fluids. Effective over a wide pH range and has a high tolerance to calcium. Not susceptible to bacterial degradation.

### PACKING

25kg in multiwall paper bag sack.

### APPLICATIONS

The concentration used will be dependent upon fluid make up and the viscosity increase required. For controlling mud properties, the optimal concentrations are 0.25-2.0lb/bbl (0.7-5.7kg/m<sup>3</sup>).

### TRANSPORT INFORMATION

Not regulated.

如需中文版产品介绍, 欢迎与我公司销售部连悉

The above information is, to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control.

**Planet Chemicals Pte Ltd**

5 Toh Guan Road East, Singapore 608831 Tel: +(65)-6872-6291 Fax: +(65)-6872 5655